



CRUSHCRETE 
Concrete & Asphalt Shingle Recycling Center
1965 Silvex Rd. • Bethlehem, Pa 18015
610-865-1898 or 610-865-2106

MATERIAL SAFETY DATA SHEET - CC2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

NAME: Crushcrete Crushed Shingle Products (RAS)

USE & DESCRIPTION: Oxidized Asphalt Shingles and Felt Paper crushed to a fine gradation to be used in Hot Mix Asphalt

CHEMICAL FAMILY: Mixture

MANUFACTURED BY:

Crushcrete Inc.
1965 Silvex Rd
Bethlehem PA 18015

EMERGENCY TELEPHONE NUMBERS;

General Information: 610-217-3447

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: PRODUCT SHOULD NOT BE HEATED OR BURNED USING A DIRECT FLAME DEVICE.

INHALATION OF PRODUCT DUST MAY CAUSE TEMPORARY UPPER RESPIRATORY IRRITATION.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE EYE IRRITATION.

MAY CAUSE HARMFUL EFFECTS IF SWALLOWED.

UNDER NORMAL CONDITIONS OF USE, THE PRODUCT IS NOT EXPECTED TO CREATE ANY EMERGENCY HAZARDS.

HMIS Rating:

Health - *1
Flammability - 1
Reactivity - 0

NFPA Rating:

Health - 1
Flammability - 1
Reactivity - 0

POTENTIAL HEALTH EFFECTS:

Eye Contact: If dust enters eye, may cause irritation resulting in tearing, stinging, redness or swelling.

Skin Contact: Prolonged or repeated skin contact could result in absorption of hazardous components.

Ingestion: Ingestion of this product may cause irritation of the digestive tract followed by vomiting.

Inhalation: Exposure to dusts may cause irritation of the nose and throat. Use of this product in well-ventilated working conditions is not expected to cause adverse effects.

Chronic Effects/Carcinogenicity/Special/Toxic:

Can cause cancer. Can cause silicosis and other permanent lung damage.

COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS No.	% by Weight
Limestone*	1317-65-3	<50
Oxidized Asphalt	64742-93-4	<30
Mineral Granules*	NE	<40
Glass Mat Fiber	NE	<20
Glass Fibers	65997-17-3	<10
Urea Formaldehyde	9011-05-6	>0.1
Binder		
Formaldehyde	50-00-0	<0.1
Backing		
Sand*	14808-60-7	<10
Talc*	14807-96-6	<10
*Contains Crystalline Silica		
Quartz	14808-60-7	>0.1
Felt ***	NE	<30

NE = Not established

3. FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of cool water for at least 20 minutes, occasionally lifting the eye lids to ensure thorough rinsing. Get medical attention if irritation persists.

SKIN CONTACT: Clean any exposed skin with warm soapy water if possible. If not, and a waterless hand cleaner is used, it should be without pumice. Do not use solvents or thinners to remove material from skin. Get medical attention if irritation persists or develops.

INGESTION: If swallowed, do not induce vomiting. If vomiting occurs, keep head lower than hips to avoid aspiration of vomit into the lungs which can cause inflammation or pneumonitis. Call poison control center or get immediate medical attention.

INHALATION: If inhalation of dust occurs, remove person to fresh air. Drink water to clear throat or blow nose to clear. If not breathing, give artificial respiration or give oxygen by trained personnel and get immediate medical attention.

NOTES TO PHYSICIAN: Treatment should be based on removing the source of irritation with treatment of symptoms as necessary.

4. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, CO₂, or foam preferred. Avoid use of straight-stream water.

SPECIAL FIRE FIGHTING PROCEDURES: Combustible. Avoid breathing fumes. Firefighters should not enter confined spaces without wearing NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.

UNUSUAL FIRE OR EXPLOSION HAZARDS: When heated, fumes may burn if ignition source is provided. Petroleum asphalt fumes can explode if emitted in an enclosed environment and supplied with an ignition source. Burning product will cause thick black smoke.

SEE SECTION 10 FOR COMBUSTION PRODUCTS

5. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS IF MATERIAL IS SPILLED OR RELEASED: Pick up large pieces. Do not dry sweep dusts or blow with air in confined area.

WASTE DISPOSAL METHODS: Dispose in accordance with applicable Federal, State, and Local regulations. Do not burn.

6. HANDLING AND STORAGE

STORAGE TEMPERATURE: Store away from heat and all ignition sources and open flames in accordance with applicable laws and regulations. **PRODUCT SHOULD NOT BE BURNED OR HEATED USING A DIRECT FLAME DEVICE.**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Follow recommended work practices and use recommended personal protective clothing and equipment. See Section 8 of this MSDS.

7. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits*

Components Raw Products	CAS No.	OSHA		ACGIH		
		TWA	STEL	TWA	STEL	Unit
Oxidized Asphalt	64742-93-4	NE	NE	0.5***	NE	mg/m ³
Limestone**	1317-65-3	15/5**	NE	10/3**	NE	mg/m ³
Fiber Glass	65997-17-3	15/5**	NE	5	NE	mg/m ³
Formaldehyde	50-00-0	0.75	2	NE	0.3	ppm
Talc	14807-96-6	2	NE	2	NE	mg/m ³
		OSHA		ACGIH		
		TWA	STEL	TWA	STEL	Unit
Crystalline Silica	14808-60-7	See 1910.1000 Table Z.3		0.025	NE	mg/m ³
Asphalt	8052-42-4	NE	NE	0.5***	NE	mg/m ³
Wood Dust	NE	15/5**	NE	1/0.5****	NE	mg/m ³

NE= Not established

* Note: Due to the form of the product, hazardous exposures from this product are not expected to occur under normal conditions of use.

** Total Nuisance Dust/Reparable Dust (mg/m³)

*** Asphalt Fume

RESPIRATORY PROTECTION: Normally not needed in well-ventilated areas. If applicable exposure standards are exceeded or can be exceeded introduce ventilation to remove dust. If increased ventilation is not possible, use a NIOSH/MSHA approved air-purifying respirator. If concentrations are sufficiently high that this respirator is inadequate, or high enough to cause oxygen deficiency, use a positive pressure self-contained breathing apparatus (SCBA). Follow all applicable respirator use, fitting, and training standards and regulations.

VENTILATION: Use only with adequate ventilation to maintain exposures below applicable exposure limits.

EYE PROTECTION: Safety glasses with side shields must be used if eye contact is possible.

SKIN: Must wear leather or cotton gloves during handling of material.

1. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Black moist powder like ground asphalt shingles.

ODOR THRESHOLD: Not Applicable

PH: Not Applicable

BOILING POINT: >700 °F

MELTING POINT/ Freezing Point: >200 °F

INITIAL BOILING POINT AND BOLING RANGE: Not Applicable

FLASH POINT: Not Applicable

EVAPORATION RATE (BUTYL ACETATE = 1) : <0.1

FLAMMABILITY (SOLID AND GAS): Not Applicable

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS: Not Applicable

VAPOR PRESSURE: Not Applicable

VAPOR DENSITY (AIR = 1): Not Applicable

SPECIFIC GRAVITY/RELATIVE DENSITY: Variable

SOLUBILITY (IES): No data available

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Applicable

AUTOIGNITION TEMPERATURE: >460°C/860°F

DECOMPOSITION TEMPERATURE: Not Applicable

VISCOSITY: Not Applicable

2. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Keep from heat, sparks, open flame and other sources of ignition.

Avoid contact with strong oxidizing agents. **PRODUCT SHOULD NOT BE BURNED OR HEATED USING A DIRECT FLAME DEVICE.**

HAZARDOUS REACTION: Polymerization will not occur.

INCOMPATIBILTY (MATERIALS TO AVOID): Strong acids or bases, oxidizing agents and selected amines.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, ozone, hydrogen sulfide, oxides of sulfur and various hydrocarbons during heating or burning. These combustion products are not expected unless product is heated or burned.

3. TOXICOLOGICAL INFORMATION

EYE – May cause eye irritation.

SKIN – May cause skin irritation.

INHALATION – Dust may cause upper respiratory irritation.

INGESTION – May cause harmful effects if swallowed.

THE FOLLOWING COMPONENT DATA IS PROVIDED FOR USER INFORMATION:

FORMALDEHYDE

Cancer - This product may contain formaldehyde. IARC and NTP have classified formaldehyde as a human carcinogen based on sufficient evidence that formaldehyde causes nasopharyngeal cancer in humans, limited evidence for cancer of the nasal cavity and paranasal sinuses, and "strong but not sufficient evidence" for leukemia.

Acute Effects - The major acute toxic effects caused by formaldehyde exposure via inhalation are eye, nose, and throat irritation and effects on the nasal cavity. Other effects seen from exposure to high levels of formaldehyde in humans are coughing, wheezing, chest pains, and bronchitis. Ingestion exposure to formaldehyde in humans has resulted in corrosion of the gastrointestinal tract and inflammation and ulceration of the mouth, esophagus, and stomach.

Chronic Effects - In addition to cancer, exposure to formaldehyde by inhalation in humans has been associated with respiratory symptoms and eye, nose, and throat irritation. Repeated contact with liquid solutions of formaldehyde has resulted in skin irritation in humans.

SILICA

Cancer - This product contains crystalline silica (quartz). IARC has determined that crystalline silica inhaled in the form of quartz from occupational sources is carcinogenic to humans (Group 1). IARC concluded that there was sufficient evidence in humans and animals for the carcinogenicity of inhaled crystalline silica in the form of quartz from occupational sources. The NTP has classified silica as known to be a human carcinogen. The physical nature of this product may help limit any inhalation hazard from crystalline silica during application and in its moistened state.

Acute Effects - Exposure to silica dust can cause irritation of the eyes, nose and throat. Exposure to high concentrations can also cause Accelerated Silicosis causing progressive shortness of breath, fever, coughing, and weight loss.

Chronic Effects – In addition to cancer, breathing of silica over a period of time can cause damage to the lung tissue and silicosis after long exposure at low concentrations causing shortness of breath, fever, coughing, and weight loss. Prolonged and repeated exposure to respirable silica-containing dust may also cause autoimmune disease, kidney disease, tuberculosis, nonmalignant respiratory disease, and bronchitis.

OXIDIZED ASPHALT

Cancer - This product contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during grinding activities has been classified by the International Agency for Research on Cancer (IARC) as "probably carcinogenic to humans" (Group 2A). IARC also determined that there was sufficient evidence of carcinogenicity of extracts and condensates of oxidized asphalts in experimental animals. The oxidized asphalt in this product may contain small amounts of Polycyclic Aromatic Hydrocarbons (PAH's) some of which are recognized carcinogens in humans or experimental animals. Oxidized asphalt may also cause irritation of the respiratory tract.

Acute Effects - Inhalation of dust may cause nose, throat, respiratory tract, and mucous membrane irritation. Eye contact may cause severe irritation, redness, tearing, and blurred vision. If ingested, may cause mouth, throat and gastrointestinal tract irritation and upset with possible nausea, vomiting and diarrhea. See Section 8 for exposure controls.

Chronic Effects - In addition to cancer, prolonged or repeated skin contact may result in dryness and irritation of the skin. Long term skin exposure to asphalt can increase sensitivity to the sun, and may cause discoloration.

4. **ECOLOGICAL INFORMATION**

Ecotoxicity – No data available

Persistence and degradability – No data available

Bioaccumulative potential – No data available

Mobility in Soil – No data available

Other adverse effects (GHG, Ozone) - No data available

5. **DISPOSAL CONSIDERATIONS**

This product has not been regulated as a hazardous waste by the USEPA. Dispose in accordance with Federal, State, and Local regulations.

6. **TRANSPORT INFORMATION**

This product is not regulated as a hazardous material for transport under 49 CFR or for vessel transport under the IMDG Code.

UN number: Not applicable

UN Proper Shipping Name: Not applicable

Packing Group, if applicable: Not applicable

Environmental Hazards: Not applicable

Transport in bulk: Not applicable

Special Precautions: Not applicable

7. **REGULATORY INFORMATION**

TOXIC SUBSTANCES CONTROL ACT (TSCA): Some components in this product are listed on the TSCA Inventory.

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA): None

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA), TITLE III:

Section 302 Extremely Hazardous Substances: None

Section 311/312 Hazard Categories: Immediate Health; Delayed Health; Fire Hazard

Section 313 Reportable Ingredients: This material contains Formaldehyde (CAS# 50-00-0), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 373.

Disclaimer of Liability

The information and recommendations contained herein are to the best of **CRUSHCRETE, Inc.'s** knowledge and belief, accurate and reliable as of the date issued. **CRUSHCRETE, Inc.** does not warrant or guarantee their accuracy or reliability, and **CRUSHCRETE, Inc.** shall not be liable for any loss or damage arising out of the use thereof.

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy his or herself that they are suitable and complete for the user's particular use.